

Presented By: Candela Corporation
Contact Phone: (800) 922-9226
Contact E-mail: sales@candelacorp.com



Customer Name:
Project Name:
Fixture Type:



GE
Lighting

20532 - F13DBXT4/SPX41

GE Biax® T4 - Facilities; Retail Display; Hospitality; Office; Restaurant; Warehouse



CAUTIONS & WARNINGS

Caution

- Lamp may shatter and cause injury if broken
- Remove and install by grasping only plastic portion of the lamp.

NOTES

- Based on 60Hz reference circuit.
- Fluorescent lamp lumens decline during life

GENERAL CHARACTERISTICS

Lamp Type	Compact Fluorescent - Plug-In
Bulb	T4
Base	G24d-1
Wattage	13
Voltage	91
Rated Life	10000 hrs
Starting Temperature	-15 °C (5 °F)
Cathode Resistance	10.5 Ohm
LEED-EB MR Credit	530 picograms Hg per mean lumen hour
Primary Application	Facilities; Retail Display; Hospitality; Office; Restaurant; Warehouse

PHOTOMETRIC CHARACTERISTICS

Initial Lumens	900
Mean Lumens	755
Nominal Initial Lumens per Watt	69
Color Temperature	4100 K
Color Rendering Index (CRI)	82

ELECTRICAL CHARACTERISTICS

Open Circuit Voltage Across Starter	198 V
Lamp Current	0.175 A
Current Crest Factor	1.7
Supply Current Frequency	60 Hz

DIMENSIONS

Maximum Overall Length (MOL)	5.2400 in(133.1 mm)
Nominal Length	5.300 in(134.6 mm)
Base Face to Top of Lamp	4.370 in(111.0 mm)

PRODUCT INFORMATION

Product Code	20532
Description	F13DBXT4/SPX41
ANSI Code	60901-IEC-0513-1
Standard Package	BUNDLE
Standard Package GTIN	10043168205327
Standard Package Quantity	50
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	50
UPC	043168205320