

DIVERSITECH ELECTRICAL DISCONNECTS

Disconnects — Metal Case

- Fused models designed with fuses in pull out handle for easy replacement
- Fused models have indicator lights for blown fuses.
- The line, load, and ground terminals are aligned for ease of wiring.
- Reversible door which opens to either the left or right.
- Side open door opens more than 180° for maximum access and has a full dead front.
- Rain tight and sleet resistant.
- The UL Listed number is IRF9, NEMA Type 3R and the US Patent is 6,630,637.



TDDS-60

CATALOG NO.	DESCRIPTION	UOM	ORDER MULTIPLE
TDDS-30	30A Fusible Disconnect Switch	EA	1
TDDS-60	60A Fusible Disconnect Switch	EA	1
TDDS-60U	60A Non-Fusible Disconnect Switch	EA	1

Low Profile Disconnects — Metal Case

- This low profile disconnect switch is a slightly smaller design than that of the standard DiversiTech disconnects
- Side opening door with a full dead front
- Rain tight and sleet resistant
- Available with pre-installed 6' 1/2" NM whip
- The UL Listed number is IRF9, NEMA Type 3R



TEDS-12-6NM

CATALOG NO.	DESCRIPTION	UOM	ORDER MULTIPLE
TEDS-60U	60A Non-Fusible Disconnect Switch	EA	1
TEDS-12-6NM	Disconnect and Whip Combo Kit	EA	1

Disconnects — Non-Metallic Case

- 60 amp non-fusible disconnect is housed in a lightweight, non-metallic case.
- Features a side opening door with more than 180° access, full dead front, and a locking tab
- U.L. and C.U.L. Listed.



T750-P60NF

CATALOG NO.	DESCRIPTION	UOM	ORDER MULTIPLE
T750-P60NF	60A Non Fusible Disconnect Switch, Non-Metallic Case, Plastic	EA	1

FUSES

RK5 Dual Element Fuses — 250V

- Provides time delay for temporary over current conditions and motor running protection for heating and air conditioning equipment.
- Eliminates unnecessary maintenance from harmless overloads.
- U.L. Class RK 5, Standard for Safety 198E, Current Limiting Fuses
- Interrupting Rating 200,000 Amps. rms. A.C.
- UL Listed, CSA Certified



T7-CRNR40

CATALOG NO.	DESCRIPTION	UOM	ORDER MULTIPLE
T7-CRNR15	15 Amps	EA	10
T7-CRNR20	20 Amps	EA	10
T7-CRNR25	25 Amps	EA	10
T7-CRNR30	30 Amps	EA	10
T7-CRNR35	35 Amps	EA	10
T7-CRNR40	40 Amps	EA	10
T7-CRNR45	45 Amps	EA	10
T7-CRNR50	50 Amps	EA	10
T7-CRNR60	60 Amps	EA	10
T7-CRNR70	70 Amps	EA	5
T7-CRNR80	80 Amps	EA	5
T7-CRNR90	90 Amps	EA	5
T7-CRNR100	100 Amps	EA	5

RK5 Time Delay Fuses — 600V

- These fuses offer safe protection during momentary overload.
- No adapter necessary.
- U.L. Listed.



T626-HASR15

CATALOG NO.	DESCRIPTION	UOM	ORDER MULTIPLE
T626-HASR10	10 Amp	EA	10
T626-HASR15	15 Amp	EA	10
T626-HASR20	20 Amp	EA	10
T626-HASR25	25 Amp	EA	10
T626-HASR30	30 Amp	EA	10
T626-HASR40	40 Amp	EA	10
T626-HASR60	60 Amp	EA	10

Class H One Time Fuses

- Protection to lighting, heating, and other non transient circuits.
- U.L. Class H, Standard for Safety 1988, One Time Fuse
- Interrupting Rating 10,000 Amps.
- 600V
- UL Listed, CSA Certified



T7-10KOTN40

CATALOG NO.	DESCRIPTION	UOM	ORDER MULTIPLE
T7-10KOTN30	30 Amps	EA	10
T7-10KOTN35	35 Amps	EA	10
T7-10KOTN40	40 Amps	EA	10
T7-10KOTN45	45 Amps	EA	10
T7-10KOTN50	50 Amps	EA	10
T7-10KOTN60	60 Amps	EA	10
T7-10KOTN70	70 Amps	EA	5
T7-10KOTN100	100 Amps	EA	5